

Create a new load balancer

To create a new load balancer, go to the dashboard and click on Load Balancer on the left side

<https://dash.elest.io/default/Ellestio-services/load-balancer>

elestio

PROJECT: **Ellestio-services**

Services

Load Balancer

Members

Billing

Settings

Audit Trail

\$14491.50
CREDITS

\$0.2310/hour
SPENDING

[Add credits](#)

Create Load Balancer

1. Select Service Cloud Provider

HETZNER DigitalOcean Amazon Lightsail linode VULTR

2. Select Service Cloud Region

Europe North America

fsn1
Germany - Falkenstein

hel1
Finlande - Helsinki

nbg1
Germany - Nuremberg

3. Select the target services which you want to connect with load balancer

You can add up to 25 targets by selecting them in the dropdown or indicate ipv4, ipv6 or global private ip addresses of your targets.

Provider
Hetzner Cloud

Region
Europe, Germany
Falkenstein

Estimated Monthly Price*
\$10

*Estimated monthly price is based on 730 hours of usage.

Create Load Balancer

There, select your cloud provider (or BYOVM) then select your preferred region.

Then select one or multiple targets for your load balancer

3. Select the target services which you want to connect with load balancer



You can add up to 25 targets by selecting them in the dropdown or indicate ipv4, ipv6 or global private ip addresses of your targets.

elestio-nebula-one-u3.vm.elestio.app x

elestio-nebula-two-u3.vm.elestio.app x

elestio-nebula-three-u3.vm.elestio.app x

x

▼

☒ elestio-nebula-one-u3.vm.elestio.app

☒ elestio-nebula-two-u3.vm.elestio.app

☐ haproxy-internal-smtp-u3.vm.elestio.app

☐ elestio-doc-u3.vm.elestio.app

☒ elestio-nebula-three-u3.vm.elestio.app

☐ minio-lux-u3.vm.elestio.app

☐ appdrag-uptime-u3.vm.elestio.app

☐ elestio-nodebb-u3.vm.elestio.app

Targets can be services in the same project, or any other target pointed by cname, IPV4, IPV6 or global private IP. You can mix targets from several providers/datacenters, this way you can improve your reliability. Since it's possible to point to the global private ip, your targets don't have to be exposed on internet and can be configured to be reached only through the load balancer.

4. Forwarding Rules



Set how traffic will be routed from the Load Balancer to your service. At least one rule is required.

Load Balancer			Target		
Protocol	Port		Protocol	Port	
HTTP ▼	80	→	HTTP ▼	3000	
Protocol	Port		Protocol	Port	
HTTPS ▼	443	→	HTTP ▼	3000	
Add Another					

Next, configure your forwarding rules from the load balancer to the targets. All incoming traffic will be sent to targets based on the rules defined below, the load balancer will use the "least connections" algorithm to decide where to send the traffic, taking account of target health and current load of targets.

It's possible to route TCP, UDP, HTTP & HTTPS traffic from the load balancer to the targets. It's possible to contact the targets over a different protocol if needed, for example from HTTPS on port 443 received on the load balancer to HTTP on port 3000 on the target, this is a very common use case when deploying an application with high availability.

5. Provide Load Balancer Name



The load balancer name cannot be changed afterwards.

Name*

lb-cuaqm

Next, give a name to your load balancer, it cannot be changed, but you can add additional custom domain names to it.

From there you can click on **"Create Load Balancer"** button; or check the optional advanced configuration below.

6. Advanced Configuration

^ Close Advanced Configuration

6.1 SSL/TLS Configuration (Optional)



To activate HTTPS / TLS / SSL on custom domain names on your service you must indicate the domain name(s) in the list below. You will also need to create a DNS entry on your domain name (from your registrar control panel) pointing to your service. You must create an A record for your domain or subdomain pointing to the ip of your service

google.com x yahoo.com x mysite.net x

Enter domain/sub domain (hit 'Enter' to add)

In advanced options, you can add up to 1000 custom domain names per load balancer

More advanced options are available to fine tune your load balancer:

6.3 Sticky Session

☐ Enable Sticky Session

6.4 Proxy Protocol

☐ Enable Proxy Protocol

6.5 Log Traffic

☒ Enable Log Traffic

6.6 Output cache (In seconds)

0

6.7 Host Header



\$http_host

6.8 IP Rate Limiter

☐ Enable Rate Limiter

6.9 Edit HTTP/HTTPS header

a. Set output headers

Key	Value
<input type="text" value="key"/>	<input type="text" value="value"/>
	
 Add Another	

b. Remove response headers

Enter headers (hit 'Enter' to add)

Sticky sessions: useful for backends that require visitors to be always forwarded to the same node for session management.

Proxy Protocol: forward the original visitor ip address to the backend, Switching proxy protocol on for targets that do not support it will render the whole service inaccessible. Alternatively the original visitor IP is available in the header "x-forwarded-for".

Log traffic: log all the traffic (visible in the log tab)

Output cache: Serve cache for a duration configured in seconds for all GET requests

Host header: by default (\$http_host) will pass to the targets the original host received by the load balancer, this can be defined to a fixed value expected by the targets if required.

IP Rate Limiter: limit the maximum number of requests allowed per second per IP address.

Add/Edit HTTP headers: allow to add or edit http headers returned by the targets to the visitors

Remove response headers: allow to remove http headers returned by the targets to the visitors

To achieve full HA you will need at least 2 load balancers in different regions and point your DNS to both load balancers with round robin DNS entries.

Revision #4

Created 30 March 2022 22:52:13 by Joseph Benguira

Updated 30 March 2022 23:53:45 by Joseph Benguira